

TE Internal #: 1932788-1 B, 2.0, Micro Profile, Receptacle, 1 Port, Top, Reverse Right Angle, Tape & Reel, Offset, Surface Mount, Cable-to-Board, 5 Position, USB Connectors

View on TE.com >



Connectors > Audio & Video Connectors > USB Connectors



USB Adapter Type: **B**

USB Version: 2.0

Connector Profile: Micro

Connector & Housing Type: Receptacle

Number of Ports: 1

Features

Product Type Features

Integral Locking Latch	Without
USB Adapter Type	В
USB Version	2.0
Connector & Housing Type	Receptacle
Connector System	Cable-to-Board
Connector & Contact Terminates To	Printed Circuit Board
USB Connector Type	Micro USB 2.0 Type-B
Configuration Features	
Number of Ports	1
Number of Positions	5
Body Features	
Shell Plating Finish	Matte
Shell Plating Material	Tin over Nickel
Offset	0 mm

1932788-1

B, 2.0, Micro Profile, Receptacle, 1 Port, Top, Reverse Right Angle, Tape & Reel, Offset, Surface Mount, Cable-to-Board, 5 Position, USB Connectors



Connector Profile	Micro
Contact Features	
Contact Mating Area Plating Material Thickness	.76 μm[29.52 μin]
Contact Mating Area Plating Material	Gold (Au)
Contact Current Rating (Max)	1.8 A
Termination Features	
Termination Post & Tail Length	.8 mm[.031 in]
Termination Method to PCB	Surface Mount
Mechanical Attachment	
Locking Feature	Without
PCB Mount Location	Тор
PCB Connector Seating	Offset
PCB Mount Retention Type	Hold-Down
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Thermoplastic
Housing Color	Black
Body Orientation	Reverse Right Angle
Centerline (Pitch)	.65 mm[.025 in]
Dimensions	
PCB Thickness (Recommended)	.8 – 1. mm[.031 – .039 in]
Usage Conditions	
Soldering Temperature (Max)	260 °C[500 °F]
Mating Cycles (Max)	10000
Operating Temperature Range	-30 – 85 °C[-22 – 185 °F]
Operation/Application	
Halogen Free	No
Assembly Process Feature	Without Pick and Place Cover
Circuit Application	Power & Signal
Industry Standards	
Industry Standard	USB 2.0
Moisture Sensitivity Level	1

1932788-1

B, 2.0, Micro Profile, Receptacle, 1 Port, Top, Reverse Right Angle, Tape & Reel, Offset, Surface Mount, Cable-to-Board, 5 Position, USB Connectors



UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	1000
Packaging Method	Tape & Reel
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
EU REACH Regulation (EC) No. 1907/2006 Halogen Content	(247) Candidate List Declared Against: JUNE 2024 (241)

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Customers Also Bought



1932788-1

B, 2.0, Micro Profile, Receptacle, 1 Port, Top, Reverse Right Angle, Tape & Reel, Offset, Surface Mount, Cable-to-Board, 5 Position, USB Connectors







Documents

Product Drawings MICRO USB, TYPE B, REVERSE

English

CAD Files 3D PDF

3D

Customer View Model ENG_CVM_CVM_1932788-1_6.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1932788-1_6.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1932788-1_6.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages 5-1773464-3_Quick_Reference_Guide_Micro_USB_Connectors

English

Product Specifications
Product Specification

English